

Product information | Sanuki

Unique character, hard, durable, versatile, environmentally friendly, maintenance-free

Product description

Sanuki is a variant of Marugame and is a panel made of laminated Marugame slats. We coat the carbon layer to prevent staining, without compromising the unique character of the robust wood. Sanuki is available as a solid all-sided charred panel or as slats glued to MDF or plywood. Sanuki is dimensionally stable and is not only a durable solution for wall coverings, it is also very suitable for making original furniture, doors and other objects.

Sanuki is a natural product. This means that individual planks may differ from one another.



Sanuki

Type of wood

Sanuki is produced by Accoya and made from Radiata Pine, which is a fast-growing pine species. The wood is modified using a (non-toxic) acetylation process. The sustainability of Accoya® wood is Class 1 and it has extensive quality certificates (including KOMO, RAL, BBA and WDMA) as well as a cradle-to-cradle gold certification. The wood has a lifespan of at least 50 years above ground and 25 years in direct contact with soil and in fresh water.

Coating

The Sanuki carbon layer is coated with Bito Hard, which is a hard coating. Bito ensures that the carbon layer becomes slightly more matt in appearance and tougher and it stops the carbon from staining. Ideal for interior applications.

Dimensions

We supply Sanuki planks in the following sizes as standard:

Thickness: at least 23mm
Width: up to 800mm
Length: up to 3m

Custom sizes are also available at an additional charge. The standard delivery time is 6-8 weeks, but do enquire about the available options!

Technical specifications

- Application: interior applications only
- Wood type: Pinus Radiata
- Origin of wood: New Zealand
- Surface texture: as per sample
- Profile: Our products have a squared profile as standard. Alternative profiles available on consultation.
- Mounting method: depends on the application. The best solution is found through consultation. We will be happy to provide technical advice regarding the best mounting method to meet your requirements.

Sanuki raw

It is possible to supply a variant of Sanuki panels with a rough cut instead of a smooth finish. With this method, the saw cuts are visible in the carbon layer. This gives the panels an extra robust look.

Maintenance

In general, Sanuki does not require any maintenance. Carefully remove dust with a feather duster or a soft, lint-free cloth, if necessary. Any stains can be carefully removed with a mild soap and cloth. We do not recommend using chemical detergents.

Do not try to char any damaged areas yourself! We do not recommend painting over these areas with black paint as the result is usually not satisfactory. The appearance of paint is different from the sheen of the carbon layer. In cases of (major) damage, please contact us for repair options.

Uitvoering

Sanuki panels are available in various designs, e.g. panels with rounded or squared slats. The images below show the difference. The width of the slats can vary between 45 mm and 150 mm, depending on your requirements. The slats can be placed horizontally or vertically. Note: the panels are always rounded on all sides.



Sanuki with rounded slats (45 mm wide)



Sanuki with squared slats (45 mm wide)

Sanuki is not only a durable solution for wall coverings, it is also very suitable for making original furniture, doors and other objects.

Applications

