

SPECIFICATIONS KAZURA ZWARTHOUT I SHOU SUGI BAN JANUARY 2022

45.31.10-A CARPENTRY, FRAMEWORK, SAWN WOOD

0. CARPENTRY FRAMEWORK

Framework: preserved,
Vertical or horizontal, bevelled
painted black for open wall cladding
Frame distance (c.t.c.) (m): max. 0.6
Joints: mechanical fastening with screws

1. SAWN CONIFEROUS WOOD (NEN 5466+a03)

Zwarthout I Shou Sugi Ban

| | |
|-----------------------|--|
| Supplier: | Zwarthout I Shou Sugi Ban www.zwarthout.com contact@zwarthout.com Middelweg 85 3956TL Leersum, the Netherlands +31 343 76 89 59 |
| Wood product | Pinus Radiata, thermally modified |
| Certification | FSC |
| Quality grade: | A2 |
| Surface treatment: | Zwarthout I Shou Sugi Ban, |
| type | Kazura |
| Profile: | as approved sample |
| Thickness (mm): | 22 mm nominal |
| Width (mm): | 50-200 mm |
| Moisture content (%): | 8-12 % |
| Preservation: | Kazura |
| • Marugame type | burnt |
| • Coating: | None or Bito White |

Fastening materials:

- 410 stainless steel screws 4x50 black head (length 2.5 x plank thickness)