

SPECIFICATIONS SAKAIDE ZWARTHOUT I SHOU SUGI BAN JANUARY 2022

45.31.10-A CARPENTRY, FRAMEWORK, SAWN WOOD

0. CARPENTRY FRAMEWORK

Framework: preserved,
Vertical or horizontal, bevelled
painted black for open wall cladding
Frame distance (c.t.c.) (m): max. 0.6
Joints: mechanical fastening with screws

1. SAWN CONIFEROUS WOOD (NEN 5466+a03)

Zwarthout I Shou Sugi Ban,
Supplier: Zwarthout I Shou Sugi Ban
www.zwarthout.com
contact@zwarthout.com
Middelweg 85
3956TL Leersum, the Netherlands
+31 343 76 89 59

Wood product Douglas
Quality grade: B
Surface treatment: Zwarthout I Shou Sugi Ban,
type Sakaide exterior Sakaide, Douglas, dosse, burned,
brushed, oiled or lacquered
Profile: as approved sample
Thickness (mm): 19-22 mm nominal
Width (mm): 50-200 mm
Moisture content (%): 10-18%
Coating: Sakaide interior: Bito Clear
Sakaide exterior: Bito Orange

Fastening materials:

- Stainless steel screws 4x50 black head (all types)
- Black-headed nails